BRADFORD WHITE GAS-FIRED WATER HEATERS

Bradford White

Residential Energy Saver Gas-Powered Direct Vent Thru-The-Wall Hot Water Heaters

FEATURES:

- Power vented for positive exhaust during main burner operation. Assembly design blows exhaust gases out of the building directly eliminating the need for conventional chimneys or expensive flue systems.
- Electronic ignition eliminates constant burning pilot resulting less gas consumption.
- 2” PVC, ABS and CPVC vent permits horizontal venting for lengths up to 30 ft. with three 90° elbows.
- 3” PVC, ABS and CPVC vent permits horizontal venting for lengths up to 90 ft. with three 90° elbows.
- Vertical venting through the roof to a height of 22 ft. when using 2” PVC, ABS and CPVC or 40 ft. using 3” PVC, ABS and CPVC.
- Vitraglas® lined tank with ceramic porcelain-like coating resists corrosion and provides a tough interior surface for long life.
- Protective magnesium anode rod to neutralize the corrosive effect of water chemicals, fight rust and assure long tank life
- Hydrojet® Total Performance System reduces cold inlet sediment build-up. Also increases 1st hour hot water delivery and minimizes temperature build-up at the top of the tank.
- Dielectric waterway fittings with special water heater nipples for long life.
- 1” non-CFC foam insulation covering the sides and top to slow heat loss. Also increases jacket rigidity.
- Fully automatic controls offer selection at your fingertips. Includes a built-in energy cut-off switch to prevent abnormally high temperatures. Built-in gas pressure regulation for added safety.
- Brass drain valve.
- T&P valve relief valve.
- Flue baffle design maximizes the amount of heat absorbed in the lower portion of the tank. Prevents heat loss during standby by minimizing air movement.
- Warranty: 6 year or 10 year on stainless steel tank with rolled and welded continuous seam to protect glass lining. 6 year limited warranty on parts.
- Design certified by CSA International (formerly AGA/CGA).

NAT GAS MODELS

Cap. Gal.	Nat & LP Input BTU	Recovery Rate GPH	Style	Floor to Flue Conn.	Jacket Dia.	Vent	Wt.	Mfr#	Item#
40	40,000	43	Lowboy	58-1/2	20”	2”	166 lb.	M-I-TW-40L6BN	MITW40L6BN
48	40,000	43	Lowboy	58-1/2”	22”	2”	185 lb.	M-I-TW-50L6BN	MITW50L6BN

LP GAS MODELS

40	40,000	43	Lowboy	58-1/2	20”	2”	166 lb.	M-I-TW-40L6BN	MITW40L6CX
48	40,000	43	Lowboy	58-1/2”	22”	2”	185 lb.	M-I-TW-50L6BN	MITW50L6CX

NOTE: Recovery rate is at 90°F rise.

Call your Local Branch for Price and Availability.